

# BirdNet Strain Gauge

## Slave Mote for Strain Gauge

### Specification

Specification		Value	Remark
<b>Wireless Network</b>	Service	▪ IEEE802.15.4e TSCH	
	Frequency Band	▪ 2.4000GHz ~ 2.4835GHz	
	NO. of Channel	▪ 15 Channels	
	Modulation	▪ DSSS	
	Data Rate	▪ 250kbps	
	Signal Power	▪ 0 or 8 dBm (Selectable)	
<b>Hardware &amp; Software</b>	CPU	▪ ARM Cortex-M3 32bit	
	SRAM	▪ 72KB	
	Flash Memory	▪ 512KB	
	Antenna	▪ 5dBi	N-type
	Input Power	▪ 외장형 2차 배터리 팩 사용	별도 구매 필수
	ESD Protection	▪ Contact : ±8KV, Air : ±15KV	
	External port for Sensor	▪ Strain Gauge or Load Cell x 1ea (WB Type)	
<b>Housing</b>	Material	▪ Aluminum Anodizing	
	Size	▪ 98mm(w) x 64mm(h) x 34mm(d)	안테나 제외
	Weight	▪ < Max. 180g	
<b>Environment</b>	Temperature	▪ -40°C ~ 85°C	
	Humidity	▪ 10 ~ 90%	Non-Condensing

## BirdNet Strain Gauge Slave Mote for Strain Gauge

### ■ Product Image



#### 주요 특징

- ❖ Strain Gauge 및 Load Cell 전용
- ❖ 지원 센서 : Wheatstone Bridge 구조, 저항값 350Ω
- ❖ 산업용 2차 배터리 팩 사용
- ❖ Enclosure 인증
  - UL 50 & CSA C22.2 No.94.1-15
  - IP 65